



Branscome Confidential

This document is the property of Branscome and may not be copied or disclosed to others without authorization.

Subject:	SH- 5 Respiratory Protection	Page - 1 -
Revised: 05/15/12		Effective Date: 02/01/13

Summary

In order to reduce the exposure to potential hazards in the air, respiratory protection may be needed for affected Branscome employees. OSHA requires that employers evaluate their work tasks to determine if atmospheric contaminants, such as dusts, mists, fumes and vapors, that could cause occupational disease are present. Where these are present, the employer must institute engineering controls or implement a respiratory protection program. Branscome employees do not generally wear respiratory protection, but may need to when engaged in work activities that cause nuisance dust.

1.0 Purpose

The purpose of this program is to:

- Identify a Respirator Program Administrator to enforce the program and provide employees with guidance in the respirator selection and use process;
- Provide instructions to all affected employees; and
- Comply with OSHA regulations and other applicable laws

2.0 Scope

This program applies to all Branscome Company employees.

3.0 Roles & Responsibilities

3.1 Management - Branscome is required to develop, implement, maintain and enforce the Respiratory Protection Program. Management will ensure that the resources are available to provide employees with the proper training and a variety of respirators to choose from.

3.2 Supervisor/Foreman shall:

- Help implement, maintain and enforce the Respiratory Protection Program;
- develop task -specific procedures for tasks where employees are required to wear respirators;
- Monitor Respirator-related activities to ensure that they are being properly implemented and procedures are being followed after implementation; and
- Periodically audit the program to ensure continued effectiveness.

3.4 The Director of Safety shall administer or oversee the respiratory protection program and conduct the required evaluations of program effectiveness.



Branscome Confidential

This document is the property of Branscome and may not be copied or disclosed to others without authorization.

Subject:	SH- 5 Respiratory Protection	Page - 2 -
Revised: 05/15/12		Effective Date: 02/01/13

3.5 Safety Specialist - will monitor day-to-day activities regarding respirator use. This includes working with the site Supervisors to establish safe work procedures for respiratory protection equipment that will ensure proper respiratory protection when needed.

When assessing tasks, the Safety Specialist will consider the following:

- The nature of the hazard;
- The physical and chemical properties;
- Adverse health effects of the respiratory hazard;
- Employee exposure levels;
- Results of sampling of airborne concentrations of contaminants;
- The warning properties of the material; and
- The physical characteristics, functional capabilities and limitations of the various types of respirators.

The Safety Specialist will also provide information (Appendix D) to employees who wear respirators on a voluntary basis.

3.6 Supervisors/Foremen – Supervisors/Foremen will work with the Safety Specialist to ensure that all respiratory protection equipment is being used properly and to provide guidance to employees who are required to use respirators.

3.7 Employees - Employees are responsible for the following:

- Understanding the requirements of this policy and procedure;
- Attending all required training sessions;
- Understanding all instructions provided by the manufacturer on use, care and warnings regarding the respirator's limitations;
- Wearing the device properly in all situations when it is required;
- Cleaning and maintaining air-purifying respirators that are assigned to each individual; and
- Storing respirators in a clean dry location that is not exposed to light, dust and chemical contamination.

4.0 Definitions

4.1 Filtering Facepiece (Dust Mask) - A negative pressure particulate respirator with a filter as an integral part of the face-piece or with the entire face-piece composed of the filtering medium.

4.2 Loose-Fitting Facepiece - A respirator face covering that is designed to form a partial seal with the face.



Subject:	SH- 5 Respiratory Protection	Page - 3 -
Revised: 05/15/12		Effective Date: 02/01/13

- 4.3 Tight-Fitting Facepiece - A respirator face covering that forms a complete seal with the face.
- 4.4 Particulate Respirator - Generally called “dust masks”, these fall into nine different classes. Each class has three levels of filter efficiency (95, 99 and 99.97%), and three categories of filter degradation (N, R and P). All nine classes filter the same particle size (0.3 micrometers aerodynamic mass median diameter). None is to be used for chemical exposure or in oxygen-deficient environments.
- 4.5 Physician or Other Licensed Health Care Professional - An individual whose legally permitted scope of practice allows him or her to independently provide or be delegated the responsibility to provide some or all of the medical services needed to authorize employees to use respirators.

5.0 References

- 29 CFR 1910.134 – Respiratory Protection
- 29 CFR 1910.134 – Respiratory Protection – Appendix D - Information for Employees Using Respirators When Not Required Under the Standard

6.0 Program

6.1 Selection of Respirators

When respirators are required by employees, or when an employee wishes to wear a filtering facepiece for comfort or convenience, the program administrator will select the proper unit for the task. Employees may not bring in respirators from home to use in the workplace.

Only respirators having NIOSH approval for the specific hazard(s) shall be selected. The selection of a proper respirator will be determined by the following:

- Nature of the respiratory hazard;
- The capabilities and limitations of respirators;
- Warning properties of the contaminant; and
- Physical and chemical properties of the contaminant;

6.3 Medical Evaluation

6.3.1 Using a respirator may place a physiological burden on employees that varies with the type of respirator worn, the job and workplace conditions in which the respirator is used, and the medical status of the employee. Prior to being fit tested, the employee must complete the Medical



Branscome Confidential

This document is the property of Branscome and may not be copied or disclosed to others without authorization.

Subject:	SH- 5 Respiratory Protection	Page - 4 -
Revised: 05/15/12		Effective Date: 02/01/13

Questionnaire and be examined by a medical professional to determine the employee's fitness to use a respirator.

6.3.2 The medical questionnaire and examinations shall be administered confidentially during the employee's normal working hours or at a time and place convenient to the employee. The medical questionnaire shall be administered in a manner that ensures that the employee understands its content.

6.4 Usage

6.4.1 Branscome will provide effective training to all employees who are required to wear respirators. Training will include:

- Limitations and capabilities of the respirator;
- Proper use and care of respirator; and
- Maintenance and storage procedures.

As part of training and prior to initial respirator use, employees must be fit tested, using the respirator that they will be expected use on the job. Fit testing shall be repeated annually to ensure a proper respirator fit.

6.4.2 User Information

The wearer of a respirator must check the seal of the face piece prior to each entry into a hazardous atmosphere to ensure proper protection. Employees will not wear respirators when facial hair interferes with the sealing surface of the device.

Employees who must wear corrective glasses and a full-face respirator will be provided with corrective glass inserts for the full-face respirator. These corrective glass inserts will be provided at no cost to the employee.

6.5 Voluntary Respirator Use

Employees only using dust masks or filtering face pieces for comfort or convenience will be provided with the information located in Appendix D of the OSHA Standard in lieu of a formal training course.

6.5.1 Voluntary respirator use is allowed by Branscome employees for the comfort and convenience of employees. This is only allowed for work situations that have been evaluated and determined to be below the



Branscome Confidential

This document is the property of Branscome and may not be copied or disclosed to others without authorization.

Subject:	SH- 5 Respiratory Protection	Page - 5 -
Revised: 05/15/12		Effective Date: 02/01/13

permissible exposure limit (PEL) or action level of the appropriate contaminant.

- 6.5.2 Selection of Respirator - Respirators chosen for voluntary use must not cause any hazard to employees. Employees may not bring in respirators from home to use in the workplace.
- 6.5.3 Filtering Facepiece Use - Filtering face-pieces or dust masks are for the general purpose of preventing dust particles from entering the employee's respiratory system. These may be used by employees to protect from paper dust, dirt or any other non-toxic dust. The use of these devices does not require a medical evaluation. These devices are disposable and therefore do not need to be cleaned and stored. They are merely disposed of after each use.
- 6.5.4 Appendix D - Management will provide each voluntary user with the following information:
 - Information contained in Appendix D;
 - Manufacturer's information on use, maintenance, cleaning, care, limitations and warnings; and
 - Each employee will sign a copy of the Appendix D statement if they plan to voluntarily use a respirator.

7.0 Training

All employees shall receive training in the Respiratory Protection Program during the New Employee Safety Orientation Program. Specific training on the use of respirators, the requirements for maintaining respirators, identifying locations where respirators are required shall be provided the employee by his department. Training must be completed prior to the assignment of any work requiring the use of respirators.

8.0 Documentation

- 8.1 To ensure that this Respiratory Program is thoroughly understood and properly used, its application shall be regularly reviewed during normal departmental self-auditing activities. These audits shall be documented and copies sent to the Safety Specialist.
- 8.3 The Safety Department shall perform a thorough documented annual evaluation of aspects of the Respiratory Protection Program, including its applications. This document will be forwarded to site management for review and approval. Signed



Branscome Confidential

This document is the property of Branscome and may not be copied or disclosed to others without authorization.

Subject:	SH- 5 Respiratory Protection	Page - 6 -
Revised: 05/15/12		Effective Date: 02/01/13

copies to be sent to the Director of Safety and shall be maintained on file for three years.

- 8.4 If a violation of this program occurs, the supervisor of the work activity being performed shall initiate and document an investigation in accordance with the Incident Investigation Procedure.

9.0 Document History

Number	Effective Date	Revision	Author
Original	May, 2006		Circle Safety
Revision 1	January, 2012		Alvin Trotman
Revision 2	May, 2012	Add voluntary use restrictions. Add medical evaluation requirement. Add Appendix A – Fit Test Protocol Add Appendix B – User Seal Check	Alvin Trotman
Revision 3	July, 2012	Remove voluntary use restrictions Add Appendix A – Fit Test Protocol Add Appendix B – User Seal Check	Alvin Trotman
Revision 4	February, 2013	To correct the Revision date of Revision 3	Alvin Trotman



Subject:	SH- 5 Respiratory Protection	Page - 7 -
Revised: 05/15/12		Effective Date: 02/01/13

Appendix A

Fit Test Protocol

1. The test subject shall be allowed to pick the most acceptable respirator from a sufficient number of respirator models and sizes so that the respirator is acceptable to, and correctly fits, the user.
2. Prior to the selection process, the test subject shall be shown how to put on a respirator, how it should be positioned on the face, how to set strap tension and how to determine an acceptable fit. A mirror shall be available to assist the subject in evaluating the fit and positioning of the respirator. This instruction may not constitute the subject's formal training on respirator use, because it is only a review.
3. The test subject shall be informed that he/she is being asked to select the respirator that provides the most acceptable fit. Each respirator represents a different size and shape, and if fitted and used properly, will provide adequate protection.
4. The test subject shall be instructed to hold each chosen facepiece up to the face and eliminate those that obviously do not give an acceptable fit.
5. The more acceptable facepieces are noted in case the one selected proves unacceptable; the most comfortable mask is donned and worn at least five minutes to assess comfort. Assistance in assessing comfort can be given by discussing the points in the following item A.6. If the test subject is not familiar with using a particular respirator, the test subject shall be directed to don the mask several times and to adjust the straps each time to become adept at setting proper tension on the straps.
6. Assessment of comfort shall include a review of the following points with the test subject and allowing the test subject adequate time to determine the comfort of the respirator:
 - (a) Position of the mask on the nose
 - (b) Room for eye protection
 - (c) Room to talk
 - (d) Position of mask on face and cheeks



Branscome Confidential

This document is the property of Branscome and may not be copied or disclosed to others without authorization.

Subject:	SH- 5 Respiratory Protection	Page - 8 -
Revised: 05/15/12		Effective Date: 02/01/13

7. The following criteria shall be used to help determine the adequacy of the respirator fit:
 - (a) Chin properly placed;
 - (b) Adequate strap tension, not overly tightened;
 - (c) Fit across nose bridge;
 - (d) Respirator of proper size to span distance from nose to chin;
 - (e) Tendency of respirator to slip;
 - (f) Self-observation in mirror to evaluate fit and respirator position.
8. The test subject shall conduct a user seal check, either the negative and positive pressure seal checks described in Appendix B-1 of this section or those recommended by the respirator manufacturer which provide equivalent protection to the procedures in Appendix B-1. Before conducting the negative and positive pressure checks, the subject shall be told to seat the mask on the face by moving the head from side-to-side and up and down slowly while taking in a few slow deep breaths. Another facepiece shall be selected and retested if the test subject fails the user seal check tests.
9. The test shall not be conducted if there is any hair growth between the skin and the facepiece sealing surface, such as stubble beard growth, beard, mustache or sideburns which cross the respirator sealing surface. Any type of apparel which interferes with a satisfactory fit shall be altered or removed.
10. If a test subject exhibits difficulty in breathing during the tests, she or he shall be referred to a physician or other licensed health care professional, as appropriate, to determine whether the test subject can wear a respirator while performing her or his duties.
11. If the employee finds the fit of the respirator unacceptable, the test subject shall be given the opportunity to select a different respirator and to be retested.
12. Exercise regimen. Prior to the commencement of the fit test, the test subject shall be given a description of the fit test and the test subject's responsibilities during the test procedure. The description of the process shall include a description of the test exercises that the subject will be performing. The respirator to be tested shall be worn for at least 5 minutes before the start of the fit test.



Subject:	SH- 5 Respiratory Protection	Page - 9 -
Revised: 05/15/12		Effective Date: 02/01/13

13. The fit test shall be performed while the test subject is wearing any applicable safety equipment that may be worn during actual respirator use which could interfere with respirator fit.
14. Test Exercises.
 - (a) Employers must perform the following test exercises for all fit testing methods prescribed in this appendix, except for the CNP quantitative fit testing protocol and the CNP REDON quantitative fit testing protocol. For these two protocols, employers must ensure that the test subjects (i.e., employees) perform the exercise procedure specified in Part I.C.4(b) of this appendix for the CNP quantitative fit testing protocol, or the exercise procedure described in Part I.C.5(b) of this appendix for the CNP REDON quantitative fit-testing protocol. For the remaining fit testing methods, employers must ensure that employees perform the test exercises in the appropriate test environment in the following manner:
 - (1) Normal breathing. In a normal standing position, without talking, the subject shall breathe normally.
 - (2) Deep breathing. In a normal standing position, the subject shall breathe slowly and deeply, taking caution so as not to hyperventilate.
 - (3) Turning head side to side. Standing in place, the subject shall slowly turn his/her head from side to side between the extreme positions on each side. The head shall be held at each extreme momentarily so the subject can inhale at each side.
 - (4) Moving head up and down. Standing in place, the subject shall slowly move his/her head up and down. The subject shall be instructed to inhale in the up position (i.e., when looking toward the ceiling).
 - (5) Talking. The subject shall talk out loud slowly and loud enough so as to be heard clearly by the test conductor. The subject can read from a prepared text such as the Rainbow Passage, count backward from 100, or recite a memorized poem or song.

Rainbow Passage

When the sunlight strikes raindrops in the air, they act like a prism and form a rainbow. The rainbow is a division of white light into many beautiful colors. These take the shape of a long round arch, with its path high above, and its two ends apparently beyond the horizon. There is, according to legend, a boiling pot of gold at one end. People look, but no one ever finds it. When a man looks for something beyond reach, his friends say he is looking for the pot of gold at the end of the rainbow.



Branscome Confidential

This document is the property of Branscome and may not be copied or disclosed to others without authorization.

Subject:	SH- 5 Respiratory Protection	Page - 10 -
Revised: 05/15/12		Effective Date: 02/01/13

- (6) Grimace. The test subject shall grimace by smiling or frowning. (This applies only to QNFT testing; it is not performed for QLFT)
- (7) Bending over. The test subject shall bend at the waist as if he/she were to touch his/her toes. Jogging in place shall be substituted for this exercise in those test environments such as shroud type QNFT or QLFT units that do not permit bending over at the waist.
- (8) Normal breathing. Same as exercise (1).

(b) Each test exercise shall be performed for one minute except for the grimace exercise which shall be performed for 15 seconds. The test subject shall be questioned by the test conductor regarding the comfort of the respirator upon completion of the protocol. If it has become unacceptable, another model of respirator shall be tried. The respirator shall not be adjusted once the fit test exercises begin. Any adjustment voids the test, and the fit test must be repeated.

B. Qualitative Fit Test (QLFT) Protocols

1. General

- (a) The employer shall ensure that persons administering QLFT are able to prepare test solutions, calibrate equipment and perform tests properly, recognize invalid tests, and ensure that test equipment is in proper working order.
- (b) The employer shall ensure that QLFT equipment is kept clean and well maintained so as to operate within the parameters for which it was designed.

2. Isoamyl Acetate Protocol

Note: This protocol is not appropriate to use for the fit testing of particulate respirators. If used to fit test particulate respirators, the respirator must be equipped with an organic vapor filter.

(a) Odor Threshold Screening

Odor threshold screening, performed without wearing a respirator, is intended to determine if the individual tested can detect the odor of isoamyl acetate at low levels.

- (1) Three 1 liter glass jars with metal lids are required.
- (2) Odor-free water (e.g., distilled or spring water) at approximately 25 deg. C (77 deg. F) shall be used for the solutions.
- (3) The isoamyl acetate (IAA) (also known as isopentyl acetate) stock solution is prepared by adding 1 ml of pure IAA to 800 ml of odor-free water in a 1 liter jar, closing



Branscome Confidential

This document is the property of Branscome and may not be copied or disclosed to others without authorization.

Subject:	SH- 5 Respiratory Protection	Page - 11 -
Revised: 05/15/12		Effective Date: 02/01/13

the lid and shaking for 30 seconds. A new solution shall be prepared at least weekly.

(4) The screening test shall be conducted in a room separate from the room used for actual fit testing. The two rooms shall be well-ventilated to prevent the odor of IAA from becoming evident in the general room air where testing takes place.

(5) The odor test solution is prepared in a second jar by placing 0.4 ml of the stock solution into 500 ml of odor-free water using a clean dropper or pipette. The solution shall be shaken for 30 seconds and allowed to stand for two to three minutes so that the IAA concentration above the liquid may reach equilibrium. This solution shall be used for only one day.

(6) A test blank shall be prepared in a third jar by adding 500 cc of odor-free water.

(7) The odor test and test blank jar lids shall be labeled (e.g., 1 and 2) for jar identification. Labels shall be placed on the lids so that they can be peeled off periodically and switched to maintain the integrity of the test.

(8) The following instruction shall be typed on a card and placed on the table in front of the two test jars (i.e., 1 and 2): "The purpose of this test is to determine if you can smell banana oil at a low concentration. The two bottles in front of you contain water. One of these bottles also contains a small amount of banana oil. Be sure the covers are on tight, then shake each bottle for two seconds. Unscrew the lid of each bottle, one at a time, and sniff at the mouth of the bottle. Indicate to the test conductor which bottle contains banana oil."

(9) The mixtures used in the IAA odor detection test shall be prepared in an area separate from where the test is performed, in order to prevent olfactory fatigue in the subject.

(10) If the test subject is unable to correctly identify the jar containing the odor test solution, the IAA qualitative fit test shall not be performed.

(11) If the test subject correctly identifies the jar containing the odor test solution, the test subject may proceed to respirator selection and fit testing.

(b) Isoamyl Acetate Fit Test

(1) The fit test chamber shall be a clear 55-gallon drum liner suspended inverted over a 2-foot diameter frame so that the top of the chamber is about 6 inches above the test subject's head. If no drum liner is available, a similar chamber shall be constructed using plastic sheeting. The inside top center of the chamber shall have a small hook attached.

(2) Each respirator used for the fitting and fit testing shall be equipped with organic vapor cartridges or offer protection against organic vapors.

(3) After selecting, donning, and properly adjusting a respirator, the test subject shall



Branscome Confidential

This document is the property of Branscome and may not be copied or disclosed to others without authorization.

Subject:	SH- 5 Respiratory Protection	Page - 12 -
Revised: 05/15/12		Effective Date: 02/01/13

wear it to the fit testing room. This room shall be separate from the room used for odor threshold screening and respirator selection, and shall be well-ventilated, as by an exhaust fan or lab hood, to prevent general room contamination.

(4) A copy of the test exercises and any prepared text from which the subject is to read shall be taped to the inside of the test chamber.

(5) Upon entering the test chamber, the test subject shall be given a 6-inch by 5-inch piece of paper towel, or other porous, absorbent, single-ply material, folded in half and wetted with 0.75 ml of pure IAA. The test subject shall hang the wet towel on the hook at the top of the chamber. An IAA test swab or ampule may be substituted for the IAA wetted paper towel provided it has been demonstrated that the alternative IAA source will generate an IAA test atmosphere with a concentration equivalent to that generated by the paper towel method.

(6) Allow two minutes for the IAA test concentration to stabilize before starting the fit test exercises. This would be an appropriate time to talk with the test subject; to explain the fit test, the importance of his/her cooperation, and the purpose for the test exercises; or to demonstrate some of the exercises.

(7) If at any time during the test, the subject detects the banana-like odor of IAA, the test is failed. The subject shall quickly exit from the test chamber and leave the test area to avoid olfactory fatigue.

(8) If the test is failed, the subject shall return to the selection room and remove the respirator. The test subject shall repeat the odor sensitivity test, select and put on another respirator, return to the test area and again begin the fit test procedure described in (b) (1) through (7) above. The process continues until a respirator that fits well has been found. Should the odor sensitivity test be failed, the subject shall wait at least 5 minutes before retesting. Odor sensitivity will usually have returned by this time.

(9) If the subject passes the test, the efficiency of the test procedure shall be demonstrated by having the subject break the respirator face seal and take a breath before exiting the chamber.

(10) When the test subject leaves the chamber, the subject shall remove the saturated towel and return it to the person conducting the test, so that there is no significant IAA concentration buildup in the chamber during subsequent tests. The used towels shall be kept in a self-sealing plastic bag to keep the test area from being contaminated.

3. Saccharin Solution Aerosol Protocol

The entire screening and testing procedure shall be explained to the test subject prior to the conduct of the screening test.



Branscome Confidential

This document is the property of Branscome and may not be copied or disclosed to others without authorization.

Subject:	SH- 5 Respiratory Protection	Page - 13 -
Revised: 05/15/12		Effective Date: 02/01/13

- (a) Taste threshold screening. The saccharin taste threshold screening, performed without wearing a respirator, is intended to determine whether the individual being tested can detect the taste of saccharin.
- (1) During threshold screening as well as during fit testing, subjects shall wear an enclosure about the head and shoulders that is approximately 12 inches in diameter by 14 inches tall with at least the front portion clear and that allows free movements of the head when a respirator is worn. An enclosure substantially similar to the 3M hood assembly, parts # FT 14 and # FT 15 combined, is adequate.
 - (2) The test enclosure shall have a 3/4-inch (1.9 cm) hole in front of the test subject's nose and mouth area to accommodate the nebulizer nozzle.
 - (3) The test subject shall don the test enclosure. Throughout the threshold screening test, the test subject shall breathe through his/her slightly open mouth with tongue extended. The subject is instructed to report when he/she detects a sweet taste.
 - (4) Using a DeVilbiss Model 40 Inhalation Medication Nebulizer or equivalent, the test conductor shall spray the threshold check solution into the enclosure. The nozzle is directed away from the nose and mouth of the person. This nebulizer shall be clearly marked to distinguish it from the fit test solution nebulizer.
 - (5) The threshold check solution is prepared by dissolving 0.83 gram of sodium saccharin USP in 100 ml of warm water. It can be prepared by putting 1 ml of the fit test solution (see (b)(5) below) in 100 ml of distilled water.
 - (6) To produce the aerosol, the nebulizer bulb is firmly squeezed so that it collapses completely, then released and allowed to fully expand.
 - (7) Ten squeezes are repeated rapidly and then the test subject is asked whether the saccharin can be tasted. If the test subject reports tasting the sweet taste during the ten squeezes, the screening test is completed. The taste threshold is noted as ten regardless of the number of squeezes actually completed.
 - (8) If the first response is negative, ten more squeezes are repeated rapidly and the test subject is again asked whether the saccharin is tasted. If the test subject reports tasting the sweet taste during the second ten squeezes, the screening test is completed. The taste threshold is noted as twenty regardless of the number of squeezes actually completed.
 - (9) If the second response is negative, ten more squeezes are repeated rapidly and the test subject is again asked whether the saccharin is tasted. If the test subject reports tasting the sweet taste during the third set of ten squeezes, the screening



Branscome Confidential

This document is the property of Branscome and may not be copied or disclosed to others without authorization.

Subject:	SH- 5 Respiratory Protection	Page - 14 -
Revised: 05/15/12		Effective Date: 02/01/13

test is completed. The taste threshold is noted as thirty regardless of the number of squeezes actually completed.

- (10) The test conductor will take note of the number of squeezes required to solicit a taste response.
- (11) If the saccharin is not tasted after 30 squeezes (step 10), the test subject is unable to taste saccharin and may not perform the saccharin fit test.

Note to paragraph 3. (a): If the test subject eats or drinks something sweet before the screening test, he/she may be unable to taste the weak saccharin solution.

- (12) If a taste response is elicited, the test subject shall be asked to take note of the taste for reference in the fit test.
 - (13) Correct use of the nebulizer means that approximately 1 ml of liquid is used at a time in the nebulizer body.
 - (14) The nebulizer shall be thoroughly rinsed in water, shaken dry, and refilled at least each morning and afternoon or at least every four hours.
- (b) Saccharin solution aerosol fit test procedure.
- (1) The test subject may not eat, drink (except plain water), smoke, or chew gum for 15 minutes before the test.
 - (2) The fit test uses the same enclosure described in 3. (a) above.
 - (3) The test subject shall don the enclosure while wearing the respirator selected in section I. A. of this appendix. The respirator shall be properly adjusted and equipped with a particulate filter(s).
 - (4) A second DeVilbiss Model 40 Inhalation Medication Nebulizer or equivalent is used to spray the fit test solution into the enclosure. This nebulizer shall be clearly marked to distinguish it from the screening test solution nebulizer.
 - (5) The fit test solution is prepared by adding 83 grams of sodium saccharin to 100 ml of warm water.
 - (6) As before, the test subject shall breathe through the slightly open mouth with tongue extended, and report if he/she tastes the sweet taste of saccharin.
 - (7) The nebulizer is inserted into the hole in the front of the enclosure and an initial concentration of saccharin fit test solution is sprayed into the enclosure using the same number of squeezes (either 10, 20 or 30 squeezes) based on the number of squeezes required to elicit a taste response as noted during the screening test. A



Branscome Confidential

This document is the property of Branscome and may not be copied or disclosed to others without authorization.

Subject:	SH- 5 Respiratory Protection	Page - 15 -
Revised: 05/15/12		Effective Date: 02/01/13

minimum of 10 squeezes is required.

- (8) After generating the aerosol, the test subject shall be instructed to perform the exercises in section I. A. 14. of this appendix.
- (9) Every 30 seconds the aerosol concentration shall be replenished using one half the original number of squeezes used initially (e.g., 5, 10 or 15).
- (10) The test subject shall indicate to the test conductor if at any time during the fit test the taste of saccharin is detected. If the test subject does not report tasting the saccharin, the test is passed.
- (11) If the taste of saccharin is detected, the fit is deemed unsatisfactory and the test is failed. A different respirator shall be tried and the entire test procedure is repeated (taste threshold screening and fit testing).
- (12) Since the nebulizer has a tendency to clog during use, the test operator must make periodic checks of the nebulizer to ensure that it is not clogged. If clogging is found at the end of the test session, the test is invalid.

4. Bitrex™ (Denatonium Benzoate) Solution Aerosol Qualitative Fit Test Protocol

The Bitrex™ (Denatonium benzoate) solution aerosol QLFT protocol uses the published saccharin test protocol because that protocol is widely accepted. Bitrex is routinely used as a taste aversion agent in household liquids which children should not be drinking and is endorsed by the American Medical Association, the National Safety Council, and the American Association of Poison Control Centers. The entire screening and testing procedure shall be explained to the test subject prior to the conduct of the screening test.

(a) Taste Threshold Screening.

The Bitrex taste threshold screening, performed without wearing a respirator, is intended to determine whether the individual being tested can detect the taste of Bitrex.

- (1) During threshold screening as well as during fit testing, subjects shall wear an enclosure about the head and shoulders that is approximately 12 inches (30.5 cm) in diameter by 14 inches (35.6 cm) tall. The front portion of the enclosure shall be clear from the respirator and allow free movement of the head when a respirator is worn. An enclosure substantially similar to the 3M hood assembly, parts # FT 14 and # FT 15 combined, is adequate.
- (2) The test enclosure shall have a 3/4 inch (1.9 cm) hole in front of the test subject's nose and mouth area to accommodate the nebulizer nozzle.
- (3) The test subject shall don the test enclosure. Throughout the threshold screening test, the test subject shall breathe through his or her slightly open mouth with



Branscome Confidential

This document is the property of Branscome and may not be copied or disclosed to others without authorization.

Subject:	SH- 5 Respiratory Protection	Page - 16 -
Revised: 05/15/12		Effective Date: 02/01/13

tongue extended. The subject is instructed to report when he/she detects a bitter taste

- (4) Using a DeVilbiss Model 40 Inhalation Medication Nebulizer or equivalent, the test conductor shall spray the Threshold Check Solution into the enclosure. This Nebulizer shall be clearly marked to distinguish it from the fit test solution nebulizer.
- (5) The Threshold Check Solution is prepared by adding 13.5 milligrams of Bitrex to 100 ml of 5% salt (NaCl) solution in distilled water.
- (6) To produce the aerosol, the nebulizer bulb is firmly squeezed so that the bulb collapses completely, and is then released and allowed to fully expand.
- (7) An initial ten squeezes are repeated rapidly and then the test subject is asked whether the Bitrex can be tasted. If the test subject reports tasting the bitter taste during the ten squeezes, the screening test is completed. The taste threshold is noted as ten regardless of the number of squeezes actually completed.
- (8) If the first response is negative, ten more squeezes are repeated rapidly and the test subject is again asked whether the Bitrex is tasted. If the test subject reports tasting the bitter taste during the second ten squeezes, the screening test is completed. The taste threshold is noted as twenty regardless of the number of squeezes actually completed.
- (9) If the second response is negative, ten more squeezes are repeated rapidly and the test subject is again asked whether the Bitrex is tasted. If the test subject reports tasting the bitter taste during the third set of ten squeezes, the screening test is completed. The taste threshold is noted as thirty regardless of the number of squeezes actually completed.
- (10) The test conductor will take note of the number of squeezes required to solicit a taste response.
- (11) If the Bitrex is not tasted after 30 squeezes (step 10), the test subject is unable to taste Bitrex and may not perform the Bitrex fit test.
- (12) If a taste response is elicited, the test subject shall be asked to take note of the taste for reference in the fit test.
- (13) Correct use of the nebulizer means that approximately 1 ml of liquid is used at a time in the nebulizer body.
- (14) The nebulizer shall be thoroughly rinsed in water, shaken to dry, and refilled at least each morning and afternoon or at least every four hours.



Branscome Confidential

This document is the property of Branscome and may not be copied or disclosed to others without authorization.

Subject:	SH- 5 Respiratory Protection	Page - 17 -
Revised: 05/15/12		Effective Date: 02/01/13

- (b) Bitrex Solution Aerosol Fit Test Procedure.
- (1) The test subject may not eat, drink (except plain water), smoke, or chew gum for 15 minutes before the test.
 - (2) The fit test uses the same enclosure as that described in 4. (a) above.
 - (3) The test subject shall don the enclosure while wearing the respirator selected according to section I. A. of this appendix. The respirator shall be properly adjusted and equipped with any type particulate filter(s).
 - (4) A second DeVilbiss Model 40 Inhalation Medication Nebulizer or equivalent is used to spray the fit test solution into the enclosure. This nebulizer shall be clearly marked to distinguish it from the screening test solution nebulizer.
 - (5) The fit test solution is prepared by adding 337.5 mg of Bitrex to 200 ml of a 5% salt (NaCl) solution in warm water.
 - (6) As before, the test subject shall breathe through his or her slightly open mouth with tongue extended, and be instructed to report if he/she tastes the bitter taste of Bitrex.
 - (7) The nebulizer is inserted into the hole in the front of the enclosure and an initial concentration of the fit test solution is sprayed into the enclosure using the same number of squeezes (either 10, 20 or 30 squeezes) based on the number of squeezes required to elicit a taste response as noted during the screening test.
 - (8) After generating the aerosol, the test subject shall be instructed to perform the exercises in section I. A. 14. of this appendix.
 - (9) Every 30 seconds the aerosol concentration shall be replenished using one half the number of squeezes used initially (e.g., 5, 10 or 15).
 - (10) The test subject shall indicate to the test conductor if at any time during the fit test the taste of Bitrex is detected. If the test subject does not report tasting the Bitrex, the test is passed.
 - (11) If the taste of Bitrex is detected, the fit is deemed unsatisfactory and the test is failed. A different respirator shall be tried and the entire test procedure is repeated (taste threshold screening and fit testing).

5. Irritant Smoke (Stannic Chloride) Protocol

This qualitative fit test uses a person's response to the irritating chemicals released in the "smoke" produced by a stannic chloride ventilation smoke tube to detect leakage into the respirator.



Branscome Confidential

This document is the property of Branscome and may not be copied or disclosed to others without authorization.

Subject:	SH- 5 Respiratory Protection	Page - 18 -
Revised: 05/15/12		Effective Date: 02/01/13

(a) General Requirements and Precautions

- (1) The respirator to be tested shall be equipped with high efficiency particulate air (HEPA) or P100 series filter(s).
- (2) Only stannic chloride smoke tubes shall be used for this protocol.
- (3) No form of test enclosure or hood for the test subject shall be used.
- (4) The smoke can be irritating to the eyes, lungs, and nasal passages. The test conductor shall take precautions to minimize the test subject's exposure to irritant smoke. Sensitivity varies, and certain individuals may respond to a greater degree to irritant smoke. Care shall be taken when performing the sensitivity screening checks that determine whether the test subject can detect irritant smoke to use only the minimum amount of smoke necessary to elicit a response from the test subject.
- (5) The fit test shall be performed in an area with adequate ventilation to prevent exposure of the person conducting the fit test or the build-up of irritant smoke in the general atmosphere.

(b) Sensitivity Screening Check

The person to be tested must demonstrate his or her ability to detect a weak concentration of the irritant smoke.

- (1) The test operator shall break both ends of a ventilation smoke tube containing stannic chloride, and attach one end of the smoke tube to a low flow air pump set to deliver 200 milliliters per minute, or an aspirator squeeze bulb. The test operator shall cover the other end of the smoke tube with a short piece of tubing to prevent potential injury from the jagged end of the smoke tube.
- (2) The test operator shall advise the test subject that the smoke can be irritating to the eyes, lungs, and nasal passages and instruct the subject to keep his/her eyes closed while the test is performed.
- (3) The test subject shall be allowed to smell a weak concentration of the irritant smoke before the respirator is donned to become familiar with its irritating properties and to determine if he/she can detect the irritating properties of the smoke. The test operator shall carefully direct a small amount of the irritant smoke in the test subject's direction to determine that he/she can detect it.

(c) Irritant Smoke Fit Test Procedure



Branscome Confidential

This document is the property of Branscome and may not be copied or disclosed to others without authorization.

Subject:	SH- 5 Respiratory Protection	Page - 19 -
Revised: 05/15/12		Effective Date: 02/01/13

- (1) The person being fit tested shall don the respirator without assistance, and perform the required user seal check(s).
- (2) The test subject shall be instructed to keep his/her eyes closed.
- (3) The test operator shall direct the stream of irritant smoke from the smoke tube toward the face seal area of the test subject, using the low flow pump or the squeeze bulb. The test operator shall begin at least 12 inches from the facepiece and move the smoke stream around the whole perimeter of the mask. The operator shall gradually make two more passes around the perimeter of the mask, moving to within six inches of the respirator.
- (4) If the person being tested has not had an involuntary response and/or detected the irritant smoke, proceed with the test exercises.
- (5) The exercises identified in section I.A. 14. of this appendix shall be performed by the test subject while the respirator seal is being continually challenged by the smoke, directed around the perimeter of the respirator at a distance of six inches.
- (6) If the person being fit tested reports detecting the irritant smoke at any time, the test is failed. The person being retested must repeat the entire sensitivity check and fit test procedure.
- (7) Each test subject passing the irritant smoke test without evidence of a response (involuntary cough, irritation) shall be given a second sensitivity screening check, with the smoke from the same smoke tube used during the fit test, once the respirator has been removed, to determine whether he/she still reacts to the smoke. Failure to evoke a response shall void the fit test.
- (8) If a response is produced during this second sensitivity check, then the fit test is passed.

Appendix B

User Seal Check Procedures

The individual who uses a tight-fitting respirator is to perform a user seal check to ensure that an adequate seal is achieved each time the respirator is put on. Either the positive and negative pressure checks listed in this appendix, or the respirator manufacturer's recommended user seal check method shall be used. User seal checks are not substitutes for qualitative or quantitative fit tests.



Branscome Confidential

This document is the property of Branscome and may not be copied or disclosed to others without authorization.

Subject:	SH- 5 Respiratory Protection	Page - 20 -
Revised: 05/15/12		Effective Date: 02/01/13

I. Facepiece Positive and/or Negative Pressure Checks

- A. Positive pressure check. Close off the exhalation valve and exhale gently into the facepiece. The face fit is considered satisfactory if a slight positive pressure can be built up inside the facepiece without any evidence of outward leakage of air at the seal. For most respirators this method of leak testing requires the wearer to first remove the exhalation valve cover before closing off the exhalation valve and then carefully replacing it after the test.

- B. Negative pressure check. Close off the inlet opening of the canister or cartridge(s) by covering with the palm of the hand(s) or by replacing the filter seal(s), inhale gently so that the facepiece collapses slightly, and hold the breath for ten seconds. The design of the inlet opening of some cartridges cannot be effectively covered with the palm of the hand. The test can be performed by covering the inlet opening of the cartridge with a thin latex or nitrile glove. If the facepiece remains in its slightly collapsed condition and no inward leakage of air is detected, the tightness of the respirator is considered satisfactory.

II. Manufacturer's Recommended User Seal Check Procedures

The respirator manufacturer's recommended procedures for performing a user seal check may be used instead of the positive and/or negative pressure check procedures provided that the employer demonstrates that the manufacturer's procedures are equally effective.

Appendix C

Appendix D: Voluntary Use Respirator Information

Respirators are an effective method of protection against designated hazards when properly selected and worn. Respirator use is encouraged, even when exposures are below the exposure limit, to provide an additional level of comfort and protection for workers. However, if a respirator is used improperly or not kept clean, the respirator itself can become a hazard to the worker. Sometimes, workers may wear respirators to avoid exposures to



Branscome Confidential

This document is the property of Branscome and may not be copied or disclosed to others without authorization.

Subject:	SH- 5 Respiratory Protection	Page - 21 -
Revised: 05/15/12		Effective Date: 02/01/13

hazards, even if the amount of hazardous substance does not exceed the limits set by OSHA standards. If your employer provides respirators for your voluntary use, or if you provide your own respirator, you need to take certain precautions to be sure that the respirator itself does not present a hazard.

You should do the following:

1. Read and heed all instructions provided by the manufacturer on use, maintenance, cleaning and care, and warnings regarding the respirators limitations.
2. Choose respirators certified for use to protect against the contaminant of concern. NIOSH, the National Institute for Occupational Safety and Health of the U.S. Department of Health and Human Services, certifies respirators. A label or statement of certification should appear on the respirator or respirator packaging. It will tell you what the respirator is designed for and how much it will protect you.
3. Do not wear your respirator into atmospheres containing contaminants for which your respirator is not designed to protect against. For example, a respirator designed to filter dust particles will not protect you against gases, vapors, or very small solid particles of fumes or smoke.
4. Keep track of your respirator so that you do not mistakenly use someone else's respirator.

I have read the above information and have been given a copy of the manufacturer's information on the type of particulate filter respirator I will have available for my voluntary use.

Employee Signature: _____

Date: _____